



GRANT OF EQUIPMENT
AUTHORIZATION



Certification
Issued Under the Authority of the
Federal Communications Commission
By:

DERYCOM CERTIFICATION SERVICES,
INC.
1100 Falcon Avenue
Glencoe, MN 55336

Date of Grant: 05/13/2026

Application Dated: 05/13/2026

**PO FUNG ELECTRONIC (HK) INTERNATIONAL GROUP
COMPANY LIMITED**

**Room 1508, 15/F, Office Tower II,
Grand Plaza, 625 Nathan Road
Kowloon,
Hong Kong**

Attention: Peter Wang ,

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is
VALID ONLY for the equipment identified hereon for use under the Commission's
Rules and Regulations listed below.

FCC IDENTIFIER: 2AJGM-DM1801PRO
Name of Grantee: PO FUNG ELECTRONIC (HK)
INTERNATIONAL GROUP COMPANY
LIMITED

Equipment Class: Licensed Non-Broadcast Transmitter Held
to Face

Notes: DMR Two Way Radio

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
EF	90	136.0 - 174.0	4.3954	2.5 PM	9K92F3E
EF ES	90	136.0 - 174.0	4.3752	2.5 PM	7K68F1D
EF ES	90	136.0 - 174.0	4.3752	2.5 PM	7K68F1W
EF	90	400.0 - 406.0	4.2364	2.5 PM	9K92F3E
EF	90	406.1 - 470.0	4.2364	2.5 PM	9K92F3E
EF ES	90	400.0 - 406.0	4.2267	2.5 PM	7K93F1D
EF ES	90	406.1 - 470.0	4.2267	2.5 PM	7K93F1D
EF ES	90	400.0 - 406.0	4.2267	2.5 PM	7K93F1W
EF ES	90	406.1 - 470.0	4.2267	2.5 PM	7K93F1W

Output power listed is conducted power. This device must be restricted to work-related operations only in an occupational/controlled RF exposure environment and must operate with a duty factor not exceeding 50%. This transmitter may operate with the antenna(s) documented in this filing in Push-to-Talk and body-worn configurations. RF exposure compliance is limited to the specific belt-clip and accessory configurations as documented in this filing, the separation distance between user and the device or its antenna shall be at least 2.5 cm. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with occupational/controlled Exposure limit and requirements. A label, as described in this filing, must be displayed on the device to direct users to specific training information for meeting occupational exposure

requirements. The highest reported SAR levels for Head and Body-worn accessories exposure conditions are 3.07 W/kg and 5.98 W/kg, respectively when operating at 50% Duty Cycle.

EF: This device may contain functions that are not operational in U.S Territories except as noted in the filing. This grant has extended frequencies as noted in the filing and Section 2.927(b) applies to this authorization.

ES: This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth.