

**Certification
Issued Under the Authority of the
Federal Communications Commission**

By:

**Bay Area Compliance Laboratory Corp.
1274 Anvilwood Avenue
Sunnyvale, CA 94089**

**Date of Grant: 07/22/2015
Application Dated: 07/22/2015**

**TYT ELECTRONICS CO., LTD
Block 39-1, Optoelectronics-information industry b
Fujian?China
Quanzhou,
China**

Attention: Jiamao Lin

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: **PODMD-380**
Name of Grantee: **TYT ELECTRONICS CO., LTD**
Equipment Class: **Licensed Non-Broadcast Transmitter Held to Face**
Notes: **DMR**

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
BF EF	90	400.0 - 406.0	5.0	2.5 PM	10K0F3E
BF EF	90	406.1 - 480.0	5.0	2.5 PM	10K0F3E
BF EF ES	90	400.0 - 406.0	5.0	2.5 PM	7K82F1D
BF EF ES	90	406.1 - 480.0	5.0	2.5 PM	7K82F1D

Output power listed is rated conducted. This device must be restricted to work-related operations only in an Occupational/Controlled RF exposure environment and must operate with a duty factor not exceeding 50%. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with Occupational/Controlled Exposure limit and requirements. A label, as described in this filing, must be displayed on the device to direct users to specific training information for meeting Occupational Exposure Requirements. Body-worn SAR compliance is limited to the specific belt-clip and accessory configurations tested for this filing and must provide at least 2.5 cm separation between the device and the user's body. The highest reported SAR values are Head: 4.08 W/kg, Body-worn: 5.86W/kg.

- BF: The output power is continuously variable from the value listed in this entry to 20%-25% of the value listed.
- EF: This device may contain functions that are not operational in U.S. Territories except as noted in the filing. This grant has extended frequencies as noted in the filing and Section 2.927(b) applies to this authorization.
- ES: This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth.