

TCB

GRANT OF EQUIPMENT
AUTHORIZATION

TCB

Certification

Issued Under the Authority of the
Federal Communications Commission

By:

Bay Area Compliance Laboratory Corp.
1274 Anvilwood Avenue
Sunnyvale, CA 94089

Date of Grant: 09/24/2015
Application Dated: 09/24/2015

TYT ELECTRONICS CO., LTD
Block 39-1, Optoelectronics-information industry b
Fujian?China
Quanzhou,
China

Attention: Jiamao Lin

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: **POD-MD380V**
Name of Grantee: **TYT ELECTRONICS CO., LTD**
Equipment Class: **Licensed Non-Broadcast Transmitter Held to Face**
Notes: **DMR**

| <u>Grant Notes</u> | <u>FCC Rule Parts</u> | <u>Frequency Range (MHZ)</u> | <u>Output Watts</u> | <u>Frequency Tolerance</u> | <u>Emission Designator</u> |
|--------------------|-----------------------|------------------------------|---------------------|----------------------------|----------------------------|
| EF | 90 | 136.0 - 174.0 | 5.62 | 2.5 PM | 9K98F3E |
| EF | 90 | 136.0 - 174.0 | 5.78 | 2.5 PM | 7K58FXD |
| EF | 90 | 136.0 - 174.0 | 5.78 | 2.5 PM | 7K58FXW |

Power output listed is conducted. This device must be restricted to work-related operations only in an Occupational/Controlled RF exposure environment and must operate with a duty factor not exceeding 50%. This transmitter may operate with the antenna(s) documented in this filing in Push-to-Talk and body-worn configurations. RF exposure compliance is limited to the specific belt-clip and accessory configurations as documented in this filing and the separation distance between user and the device or its antenna for in-front-of-face operation shall be at least 2.5 cm. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with Occupational/Controlled Exposure limit and requirements. A label, as described in this filing, must be displayed on the device to direct users to specific training information for meeting Occupational Exposure Requirements. The highest reported SAR values for face held and body-worn accessory exposure conditions are 0.26 W/Kg and 0.59 W/Kg respectively.

EF: This device may contain functions that are not operational in U.S Territories except as noted in the filing. This grant has extended frequencies as noted in the filing and Section 2.927(b) applies to this authorization.