

TCB**GRANT OF EQUIPMENT
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the
Federal Communications Commission****By:****Bay Area Compliance Laboratory Corp.
1274 Anvilwood Avenue
Sunnyvale, CA 94089****Date of Grant: 12/28/2017****Application Dated: 12/28/2017****TYT ELECTRONICS CO., LTD****Block 39-1, Optoelectronics-information****industry base, Nan'an,****Quanzhou, Fujian,,****China****Attention: Jiamao Lin****NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE,
and is VALID ONLY for the equipment identified hereon for use under the
Commission's Rules and Regulations listed below.

FCC IDENTIFIER: POD-DMR3
Name of Grantee: TYT ELECTRONICS CO., LTD
Equipment Class: Licensed Non-Broadcast Station
Transmitter
Notes: DMR Mobile Radio

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
EF	90	136.0 - 174.0	50.0	2.5 PM	11K0F3E
EF ES	90	136.0 - 174.0	50.0	2.5 PM	7K60F1E
EF ES	90	136.0 - 174.0	50.0	2.5 PM	7K60F1D
EF	90	400.0 - 406.0	35.0	2.5 PM	11K0F3E
EF	90	406.1 - 480.0	35.0	2.5 PM	11K0F3E
EF ES	90	400.0 - 406.0	35.0	2.5 PM	7K60F1E
EF ES	90	406.1 - 480.0	35.0	2.5 PM	7K60F1E
EF ES	90	400.0 - 406.0	35.0	2.5 PM	7K60F1D
EF ES	90	406.1 - 480.0	35.0	2.5 PM	7K60F1D

Output power listed is maximum conducted power at antenna terminal. This device must be restricted to work related operations in an Occupational/Controlled RF exposure Environment. End-Users must be provided with the specific training information. A label, as described in this filing must be displayed on the device to direct users to the specific training information required for meeting RF exposure requirements. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 40 cm from all persons. RF exposure compliance may be addressed at the time of licensing, as required by the responsible FCC Bureau(s), including antenna co-location requirements of Section 1.1307(b)(3). The output power is variable at 5 W & 50 W in VHF band and 5 W & 35 W in UHF band.

EF: This device may contain functions that are not operational in U.S Territories except as noted in the filing. This grant has extended frequencies as noted in the filing and Section 2.927(b) applies to this authorization.

ES: This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth.